

Model ECXP35Y

8" - 14 gauge spun aluminum ball
gold anodized

Single sheave truck, cast
aluminum revolving,
non-fouling type

2 Bronze swivel snaps
with covers per halyard

3 Sets of halyard: #10 poly

9'-6" Yardarm

3 - 9" Cast aluminum cleat

Aluminum flash collar

3000 PSI concrete

Hardwood wedges
(supplied by others)

Dry sand tightly tamped
after aligning pole

Foundation sleeve - 16 ga
hot dip galvanized steel

Steel centering wedges

1/4" Steel base plate

1/4" Steel support plate
welded to grounding
spike

Exposed height: 35'-0"

Tapered portion: 20'-0"

2-3/8"

Overall length: 38'-6"

Straight portion: 18'-6"

Cleat height: 5'-0"

Foundation: 4'-0"

3'-6"

6"

12"

16"

36"

Yardarm Dimensions

End diameter: 2"
Center diameter: 3-1/2"
Tapered length, ends: 9'-0"
Straight section: 6"
Wall thickness: .125"

Truck Detail

Aluminum body
Stainless steel ball bearings
Aluminum sheave
Cast aluminum spindle

Project:	Ground set tapered aluminum flagpole: ALLOY: 6063T6		FLAGS.COM	Date:
Location:	Exposed height: 35'-0"	Overall height: 38'-6"	1-800-858-8776	Revision:
Architect:	Ship in 2 sections	Butt diameter: 6"	1395 NW 17th Ave #112B	
Contractor:	Top diameter: 3-1/2"	Wall thickness: .156"	Delray Beach, FL 33445	
Customer:	Finish: 100 grit polish			Job: